# Daikin DZ4SE & AMST



### **Key Features - DZ4SE Condenser**

- High-efficiency Copeland® scroll compressor
- Advanced Copeland® CoreSense technology
- Copper tube/enhanced aluminum fin coil 5mm diameter on 1.5-3.5T
- High density foam compressor sound blanket
- Time-delay technology to ensure quiet reliable defrost
- Factory-installed bi-flow liquid line filter
  drior
- Factory-installed suction line accumulator
- Factory-installed compressor crank case heater
- Factory-installed high-capacity muffler
- High- and low-pressure switches
- Service valves with sweat connections and easy access to gauge ports
- Fully charged for 15' of tubing length

#### Cabinet Features - DZ4SE Condenser

- Removable grille-style top design compliant with UL 60335-2-40
- Venturi for increased velocity of airflow
- Custom Nickel Gray powder-paint finish
- 500-hour salt-spray tested
- Wire fan discharge grille
- Steel louver coil guard
- Rust-resistant screws
- Top and side maintenance access
- Single-panel access to controls with space provided for field-installed accessories
- When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)

## Key Features – AMST Air Handler

- Internal factory-installed thermal expansion valves for cooling and heat pump applications
- $\bullet$  7mm evaporator coil tube size on 11/2 31/2 Ton models and 3/8" evaporator coil tube size on 4 to 5 Ton models
- Direct-Drive, 9-speed ECM blower motor
- All-aluminum evaporator coil with high performance coated fin stock
- Coil mounting track for quick repositioning
- Optimized for use with R-410A refrigerant
- Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193
- Cabinet air leakage less than 1.4%

at 0.5 inch H2O when tested in accordance with ASHRAE standard 193

- 3 kW 25 kW electric heater kits
- Rigid SmartFrameTM cabinet
- Horizontal or vertical configuration capabilities
- 21" depth for easier attic access
- DecaBDE-free thermoplastic drain pan with secondary drain connections
- Screw-less sides and back helps to reduce condensation when installed in humid locations
- Foil-faced insulation covers the internal casing to reduce cabinet condensation
- Galvanized, leather grain-embossed finish
- Glue-less cabinet insulation retention
- Tool-less filter access

## Warranty











12 year all parts, 6 year replacement



**COMMERCIAL & RESIDENTIAL SERVICE**